

Print Beyond Limits — Direct printing on substrates up to 250 mm thick and 20 kg

Print directly onto finished products.

In addition to decorating new products, UJF200 supports custom printing on customer-supplied items, expanding your business opportunities.



Maximum Print Area and Load Capacity

UJF200-3042	UJF200-6042
- W300 mm × D420 mm × H250 mm - Max 20 kg	- W610 mm × D420 mm × H250 mm - Max 20 kg

Maximize Productivity and Creative Potential with Genuine RIP Software



RasterLink8

- Easy fluorescent colour printing
- Automatic image positioning on substrates
- Printer-to-printer colour matching

— Remote Machine Operation



MRA
(Mimaki Remote Access)

— Supports Efficient Production

Mimaki Cloud
Technology



Choose from Two Ink Types to Suit Your Application



ELH-100
Excellent Scratch
and Solvent Resistance
Rigid Ink

ELS-120
Excellent Flexibility
and Weather Resistance
Flexible Ink

SVHC-Free Ink for Greater Safety for People and the Environment

Free from substances
of very high concern (SVHC)
for human health

CMR Free

TPO Free

*EFS-150 ink is available only in SVHC-free and TPO-free formulations.

Specifications

Item	UJF200-3042	UJF200-6042
Print head	On-demand piezo head	
Print resolution	Y: 600, 900, 1200 dpi / X: 900, 1200, 1800 dpi	
Ink	Types	UV-Curable Rigid Ink ELH-100, Flexible Ink ELS-120/EFS-150, IJ Primer PR-200
	Capacity	1 L bottle / 250 ml bottle per colour
Max. print area (W×D)	300 mm × 420 mm	610 mm × 420 mm
Media	Max. thickness	250 mm
	Weight	Up to 20 kg (44.1 lb)
Interface	USB 2.0 / Ethernet 1000BASE-T	
Certifications	VCCI Class A, FCC Class A, IEC 62368-1 Certified ETL, CE Marking (EMC Directive, Low Voltage Directive, Machinery Directive), CB Certificate, RoHS, REACH, EnergyStar, EAC, RCM	
Power supply	Single-phase AC 100-120 V ±10%, 50/60 Hz ±1 Hz	
Power consumption	Max. 450 W / Standard 250 W / Min. 4.5 W or less	
Operational Environment	Temperature	20 ~ 30°C (68 to 86°F)
	Humidity	35 to 65% RH (non-condensing)
	Guaranteed Accuracy Temperature Range	20 to 25°C (68 to 77°F)
	Temperature Gradient	±10°C/h or less
Dust Level	0.15 mg/m ³ (equivalent to a typical office environment)	
Dimensions (W×D×H*)	1,380 mm x 1,166 mm x 798 mm (54.3 x 45.9 x 31.5 in)	1,680 mm x 1,166 mm x 798 mm (66.1 x 45.9 x 31.4 in)
Unit Weight	171 kg	187 kg

*Height (H) refers to the height of the main unit, excluding the ink bottle and dedicated stand.

*Specifications, design, dimensions, and other details are subject to change without notice due to technical improvements or other reasons.

Inks and substrates

- As ink properties such as adhesion and weather resistance may vary depending on the substrate, please perform a print test in advance.
- Depending on the application, primers, surface treatments, or protective finishes such as lamination may be required.

Safety notice

This product is equipped with UV irradiation equipment.

Please observe the following safety precautions when using the product.

- Do not look directly at the UV light source or expose your eyes, hands, or skin to UV light.
- Depending on the print mode, VOC emissions may occur from printed parts that have not yet been fully cured.
- Please read and follow all instructions and guidelines in the user manual.

•Some examples shown in this catalog are artificial renderings. •Specifications, designs and dimensions shown in this catalog may be subject to change without notice for technical improvements. •The corporate and merchandise names in this catalog are the trademarks or registered trademarks of the respective corporations. •Inkjet printers use extremely fine dots, so colors may vary slightly after replacement of print heads. •Also note that when using multiple printer units, colors could vary slightly from one unit to another due to slight individual differences. •Please note that descriptions and data in this catalog are as of September 2026.



Flatbed UV-LED Inkjet Printer

UJF200-3042

UJF200-6042



More Possibilities. One Printer.



Mimaki Europe B.V.

Stammerdijk 7E, 1112 AA Diemen, The Netherlands
Tel. : +31 20 4627640 | www.mimakieurope.com

EMEA Offices

Mimaki Deutschland GmbH | www.mimaki.de | Mimaki France | www.mimaki.fr
Mimaki Bompan Textile | www.mimakibompan.it | Mimaki Eurasia | www.mimaki.com.tr


Find a local reseller near you: www.mimakieurope.com/dealer-locator

More Possibilities. One Printer.

Unlock New Creative and Business Opportunities with One Printer.

The UJF200 Series delivers outstanding creative flexibility with exceptional image quality, fine detail, and vibrant colours. Automated features help streamline production workflows, improve efficiency, and reduce the need for manual intervention. The printer also supports direct printing onto thicker and heavier substrates, enabling an even wider range of applications.

From on-demand print service providers to industrial manufacturers, the UJF200 Series helps companies expand their product offerings, enter new markets, and unlock new revenue opportunities.




01 Stunning Print Quality. Fine Detail, Vibrant Colours

Sharp Reproduction of Fine Text and Lines



A high-density, high-precision printhead controls ink droplets as small as 4 pL, delivering sharp, high-quality print results.

Smooth and Beautiful Gradients



Reproduces colour tones with rich, nuanced gradients, enabling accurate skin tone reproduction and subtle tonal expression.

Achieve Even More Vibrant Colours with Fluorescent Inks

Featuring fluorescent pink and yellow inks, the UJF200 delivers highly saturated colours beyond the capabilities of standard CMYK. Create eye-catching designs and distinctive customised products that help brands and businesses stand out.



Smartphone Case



Collectible Toys



Electronic Devices

02 Boost Efficiency Through Automation

*The automation options shown below are available separately.

Automation Options for Streamlined Production

By combining these two options, the entire process, from substrate feeding and printing to product collection, becomes more labour-efficient. This enables unattended operation overnight and during holidays, allowing you to increase production volume even with a limited workforce.

Camera Option

Automatically detects the substrate's shape and position and places the print image accordingly. Reduces the need for manual positioning and alignment work.

Belt Option

*Compatible only with the UJF200-6042.

Can be connected to production-line conveyors to automate substrate feeding and collection.




*The image is for illustrative purposes only. The actual product may differ in colour, shape, or other aspects. These differences do not affect functionality or performance.

03 Improve Productivity Significantly reduce waiting time

Shorter Waiting Times


*Compared to previous models

Printer start-up time



Approx. 1 min. 30 sec.

Cleaning Time (Normal Cleaning)




Approx. 1 min. 50 sec.

Production per Hour


Colour Printing / A2 Size / Standard Mode

Previous model



**Calculated based on the time from substrate loading to unloading.

UJF200-6042



Print on white substrates, metal, and other materials while preserving their original colour and texture.